

Ergo-Express® Model 4000SHD Motorized Tug

Innovation Designed Around You

**PHS
WEST
INC.**

Technical Specifications

The Ergo-Express® Model 4000SHD | Motorized Tug is the perfect solution for moving any heavy, wheeled load.



Ergo-Express® Model 4000SHD | Motorized Tug Specifications

- Model Name and Number: 4000SHD
- Dimensions
 - Width: 26.26"
 - Length: 30.61"
 - Height: 44" to the top of the controller
- Turning Radius: 19"
- Towing Capacity: 5,000lb.
- Frame Construction: 10 Gauge CRS | ASTM A366
- Drive Wheel: 10" Diameter x 3 Wide"
 - Grey Non-Marking
 - 4-Ply Nylon, Foam-Filled
- Caster Size: 6" Diameter x 2 Wide"
 - Performa Rubber
 - Temperature Range: -45°F to +180°F (120°F continuous service)
 - Hardness: 55 (±5) Durometer Shore A Scale
- ETC/ETLC Number: UL 583:2012
 - Ed. 10 +R:25May2016, ULC C583-1974/01/01
- Controller: Microprocessor-based
- Charging System
 - 120VAC
 - 2.4 A
 - Watts: 288
 - Electrical Phase: 1
 - Charging Cord: (UL) 384516 SJT 3X14AWG 105°C 300V VW-1
 - Plug Type: 5-15P
 - Drive System Voltage: 24VDC
- Battery Specifications
 - 80 AH
 - AGM Battery: Stand-By, UPS, High-Rate, Telecomm
 - Absorbed Glass Mat (AGM) - Battery
 - Synonyms: SLA, VRLA, AGM, Absorbed Glass Mat
 - Sealed Recombinant
 - Dot Description: Wet Battery, Non-Spillable
 - Chemical Name: Sealed Lead Acid, Secondary Battery
- Drive System
 - 24 VDC, 3909 RPM, 5.00 A Maximum, PMDC
 - Electromechanical Holding Brake, rated at 70lb./in. (8.0 Nm), with override and controller feedback
 - Top Speed: 4.00 MPH
- Three Year Limited Warranty
- 24/7-365 Technical and Operational Support for the life of the product

Additional technical and operational specifications are available for custom designs.