



Wheel and Brake Service Carts

DESCRIPTION

The Wheel and Brake Service Cart was designed to provide safe transportation of aircraft wheel assemblies, brakes and required tooling, while maintaining the storage requirements of regulatory bodies (EASA, TC, FAA).

The low-profile design and lightweight swing gates ensure safety of maintenance staff during use. Foam-filled tires are available upon request.

Our Professional Engineers will work with you to determine what size service cart works best within your operation.

WHAT OUR CUSTOMERS ARE SAYING

"We find that Factory Supply is more than willing to work with us in creating safe, economical and multi-purpose designed equipment, tailored to our needs."



FACTORY
SUPPLY



PRODUCT FEATURES

- Low-profile design
- Lightweight swing gates
- Safe transportation of aircraft wheel assemblies and tools
- Enclosed versions available
- Steel or aluminum construction
- Maintains the storage requirements of regulatory bodies (EASA, TC, FAA)

BENEFITS

- Low-profile design and lightweight swing gates ensure safety of maintenance staff during use
- Foam-filled tires are available upon request
- Provides safe transportation of aircraft wheel assemblies, brakes and required tooling
- Can be configured to carry associated tire change jacks and tools
- Optional Nitrogen
- 2 year limited warranty on components
- 10 year limited warranty on structure

Wheel and Brake Service Carts

AVAILABLE ACCESSORIES

- Brake lifting hoist
- Foam-filled tires
- Solid tires
- Full hard or soft cover
- Nitrogen bottle holders
- Surge braking system
- Tool boxes



TECHNICAL SPECIFICATIONS

DF081002		
DESIGNED FOR	Transports Wheel & Brake Assemblies	
AIRCRAFT TYPE	All Aircraft Types	
MOVEMENT	Pintle, Towed	
TOWING SPEED	31 MPH / 50 KPH	
SHIPPING (DIMS)	Based Upon Customer Requirements	
DECK HEIGHT	5 3/4" / 12.7cm Or As Required	
WIDTH	116" / 294.6 cm Or As Required	
WEIGHT CAPACITY	2,500lbs / 1,134kg Or As Required	
CONFIGURATION	Based Upon Customer Requirements	
MATERIAL	Structure: Steel or Aluminum	Ramps: Steel or Aluminum
FINISH	Based Upon Customer Requirements	
WHEELS	15" / 38.1cm or 16" / 40.6cm Wheels Based on Customer Requirements	
PADDING MATERIAL	As Required	